

SPORT CHIEF RT SPECIFICATIONS



ENGINE: THUNDERSTROKE 116

Engine Type	Air-Cooled 49° V-twin
Transmission	6-speed, constant mesh / foot shift
Battery	12 volts / 18 amp/hour, 310 CCA with quick connect charge port
Bore x Stroke	103.2mm x 113mm
Clutch	Wet, multi-plate
Compression Ratio	11.0 : 1
Displacement	116 cu in / 1890 cc
Exhaust	Dual exhaust
Final Drive	Belt drive, 146 tooth
Lubrication System	Semi-dry sump
Fuel Capacity	15.1 litres
Fuel System	Closed loop / 54 mm bore
Oil Capacity	5.68 litres
Primary Drive	Gear drive wet clutch
Peak Torque	156 Nm at 3,300 rpm

SUSPENSION

Front Suspension	KYB® Inverted Telescopic Fork, 43 mm diameter, 130 mm travel
Rear Suspension	Dual FOX® Piggyback Shocks with adjustable preload, 100 mm travel

CHASSIS

Wheelbase	1640 mm
Rake/Trail	28° / 111 mm
Lean Angle (Soft)	29.5°
Seat Height	695 mm
Weight	312 kg / 322 kg (As Shipped/Running Order)
Ground Clearance	128 mm
GVWR	526 kg
Length	2301 mm

BRAKES

Brake System Type	Brembo® Individual front & rear control with ABS
Front Braking System	Dual 4 piston caliper / 320 mm semi-floating rotor
Rear Braking System	Single 2 piston caliper / 298 mm floating rotor

WHEELS & TIRES

Front Tire	Metzeler® Cruisetec® 130/60 B19 61H
Front Wheel	Sport Cast Black 19" x 3.5"
Rear Tire	Metzeler® Cruisetec® 180/65 B16 81H
Rear Wheel	Sport Cast Black 16" x 5"

STANDARD FEATURES

Lighting	LED Headlight, LED Tail/Brake/Turn Signals
Gauges	101 mm Touchscreen Powered By RIDE COMMAND with Navigation* and Bluetooth®
Controls	Cruise Control, 3 Selectable Ride Modes, Keyless Ignition, ABS, USB Charge Port

COLORS

Black Smoke
Sunset Red Smoke
Heavy Metal

For pricing and availability in your region, please contact your local Indian Motorcycle press contact. Images may show North American models and may have accessories fitted. International models may vary.

*Navigation may not be available in all countries.

