



SPECIFICATIONS

ENGINE: LIQUID-COOLED V-TWIN (60 DEGREES)

Engine	DOHC, 4-valves per cylinder, graded buckets
Transmission	6-speed, constant mesh / foot shift
Battery	12 Volt, 12AH, 240CCA, maintenance free AGM
Bore x Stroke	102mm x 73.6mm
Charging System	35 amp max output
Clutch	Assist & slip, multi-plate
Compression Ratio	12.5 : 1
Cooling System	Liquid
Displacement	1203 cc
Exhaust	2-into-1, catalyst in collector
Final Drive	Chain / 525HV3X / 116 Link
Fuel & Capacity	91 octane recommended, 13 ltr
Fuel System	Closed loop fuel injection / 60mm bore
Oil & Oil Capacity	SAE 15W60, 4.16 ltr
Primary Drive	Gear drive wet clutch
Horsepower	92 kW at 7750 rpm
Peak Torque	118 Nm at 6000 rpm

SUSPENSION

Front Suspension	ZF Sachs® Fully Adjustable Inverted Telescopic Cartridge Fork, 43mm diameter, 120 mm travel
Rear Suspension	ZF Sachs® Fully Adjustable Piggyback IFF, 120 mm travel

CHASSIS

Dry Weight	219 kg
Ground Clearance	165 mm
GVWR	430 kg
Length	2223 mm
Rake/Trail	25.3° / 100 mm
Seat Height (Laden/Unladen)	780 mm / 817 mm
Wheelbase	1524mm
Lean Angle	43°

BRAKES

Brake System Type	Individual front and rear control
Front Braking System	Brembo® Dual 320mm t5 Rotor / 4 Piston Caliper
Rear Braking System	Brembo® Single 260mm t5 Rotor / 2 Piston Caliper

WHEELS & TIRES

Front Tire	Metzeler® Sportec® 120/70ZR17 58W
Front Wheel	Cast 17 in x 3.5 in
Rear Tire	Metzeler® Sportec® 180/55ZR17 73W
Rear Wheel	Cast 17 in x 5.5 in

STANDARD EQUIPMENT

ABS, Cruise Control

COLORS

Metallic Black / Lime
Stealth Gray / Orange Burst

For pricing and availability in your region, please contact your local Indian Motorcycle press contact. Images may show North American models and may have accessories fitted. International models may vary.