

MY24 Enduro Pro	TE 300 Pro
Engine	
Engine type	Single cylinder, 2-stroke
Displacement	293.2 cc
Bore/stroke	72/72 mm
Compression ratio	-
Starter/battery	Electric starter / Lithium Ion 12,8V 2Ah
Transmission	6 gears
Fuel system	Keihin EFT, throttle body Ø 39 mm
Control	Electronic Exhaust Control
Lubrication	Electronically regulated oil injection
Gear ratios	13:33 16:30 18:26 22:26 23:23 26:22
Primary ratio	26:72
Final drive	14:45 (13:45)
Cooling	Liquid cooling
Clutch	DDS wet multi-disc clutch, BREMBO hydraulics
Ignition / Engine Management	Vitesco Technologies EMS
Chassis	
Frame	Central double-cradle-type 25CrMo4
Subframe	Aluminium reinforced Polyamide
Handlebar	ProTaper, Aluminium Ø 28/22 mm
Front suspension	WP XACT CC-USD, Ø 48 mm
Rear suspension	WP XACT-Monoshock with linkage
Suspension travel front/rear	300/300 mm
Front/rear brakes	BREMBO disc brake Ø 260/220 mm
Front/rear rims	1.60 x 21"; 2.15 x 18" EXCEL
Front/rear tyres	90/90-21"; 140/80-18" Michelin Enduro
Chain	520 X-Ring
Silencer	Aluminium
Steering head angle	63.9°
Triple clamp offset	22 mm
Wheel base	1,489±10 mm
Ground clearance	354 mm
Seat height	952 mm
Tank capacity, approx.	8.5l
Competition weight: (without fuel)	108.5 kg