

125NK Specs	
Commercial Name	125NK
Displacement	124.9CC
Bore x Stroke	/
Max power	10.4KW
Max Troque	12N.M
Comprehension ratio	11.5
Clutch	Slip Clutch
Throttle Type	Mechanical throttle
Power mode	/
Frame	
Frame	Steel tube frame
Hand Bar	All in one Handbar
Rear swing arm	Dual Swing arm
Front Rim	Aluminium RIM
Front wheel	110/70 R17 M/C
Rear wheel	140/60 R17 M/C
Front Suspension	inverted Suspension
Rear Suspension	Monoshock
Front / Rear Suspension Travel	/
Front Brake Pump	Hangte
Front Brake	292MM disc , HANGTE 4-Piston
Rear Brake Pump	Hangte
Rear Brake	220mm Disc , Single Piston
ABS&CBS	ABS
Corner ABS	/
TC	Standard (ON/OFF)
Steering damper	/
基本参数规格	
Length x width x height	/
Turning angle	/
RAKE	/
TRAIL	/
Wheelbase	/
Seat height	780mm
Ground clearance	/
Fuel capacity	12.5L
Net weight	141
电气	

Dashboards	5 " inch curved TFT , Wifi
Handbar	/
Battery	/
Auto Lamp	LED
Daylight	LED
Turning LIGHT	/
ESS	Standard
Mech Key	Mech key
BIKE NAVI	/
Q-S	/
Tire pressure	/
Heated handbar	/
Heat Cushion	/
USB /TPYE c	Standard
T-BOX	