



SPECIFICATIONS

ENGINE: LIQUID-COOLED V-TWIN (60 DEGREES)

Engine	DOHC, 4-valves per cylinder, graded buckets
Transmission	6-speed, constant mesh / foot shift
Battery	12 Volt, 12AH, 240CCA, maintenance free AGM
Bore x Stroke	102mm x 73.6mm
Charging System	35 amp max output
Clutch	Assist & slip, multi-plate
Compression Ratio	12.5 : 1
Cooling System	Liquid
Displacement	1203 cc
Exhaust	2-into-1, catalyst in collector
Final Drive	Chain / 525HV3X / 116 Link
Fuel & Capacity	91 octane recommended, 13 ltr
Fuel System	Closed loop fuel injection / 60mm bore
Oil & Oil Capacity	SAE 15W60, 4.16 ltr
Primary Drive	Gear drive wet clutch
Horsepower	92 kW at 7750 rpm
Peak Torque	118 Nm at 6000 rpm

SUSPENSION

Front Suspension	Inverted Telescopic Cartridge Fork, 43mm diameter, 150 mm travel
Rear Suspension	Monotube IFP, 150 mm travel

CHASSIS

Dry Weight	228 kg
Ground Clearance	183 mm
GVWR	430 kg
Length	2286 mm
Rake/Trail	26.3° / 130 mm
Seat Height <small>(Laden/Unladen)</small>	815 mm / 840 mm
Wheelbase	1525 mm CHECK
Lean Angle	43° CHECK

BRAKES

Brake System Type	Individual front and rear control
Front Braking System	Brembo® Dual 320mm t5 Rotor / 4 Piston Caliper
Rear Braking System	Brembo® Single 260mm t5 Rotor / 2 Piston Caliper

WHEELS & TIRES

Front Tire	Pirelli® Scorpion Rally STR, 120/70R19 60V
Front Wheel	Wire Spoke 19 in x 3 in
Rear Tire	Pirelli® Scorpion Rally STR 150/70R18 M/C 70V
Rear Wheel	Wire Spoke 18 in x 4.25 in

STANDARD EQUIPMENT

101 mm Touchscreen powered by RIDE COMMAND with navigation & Bluetooth® Ride Modes (Rain, Standard, Sport)
Lean Angle Sensitive ABS, Stability Control, Traction Control,
Wheelie and Rear Lift Mitigation, USB Charge Port & Cruise Control

COLOR

Black Smoke

For pricing and availability in your region, please contact your local Indian Motorcycle press contact. Images may show North American models and may have accessories fitted. International models may vary. Navigation may not be available in all countries.