

## 675SR-R (2024-0528)

675SR-R (2024-0528)	
<b>POWER</b>	
Engine	3-cylinder, inline 4-stroke, liquid-cooled, DOHC
Displacement	675cc
Bore x Stroke	72x55.2 mm
Maximum Power	70kW/11000 rpm
Maximum Torque	70Nm/8250 rpm
Fuel System	BOSCH EFI
Compression Ratio	11.5:1
Transmission	CF-SC slipper assist clutch, 6-speed, wet, multi-plate
Throttle	Mechanical throttle
Top speed	>220km/h
<b>CHASSIS/SUSPENSION/BRAKES</b>	
Frame	Steel tubular frame
Swingarm	Aluminum alloy high-arch twin swingarm
Rim	Aluminum alloy
Front Tire	120/70 R17 (CST S3)
Rear Tire	180/55 R17 (CST S3)
Front Suspension	φ41 inverted suspension, fully adjustable, KYB
Rear Suspension	monoshock rear suspension, adjustable preload & rebound, KYB
Front/Rear Suspension Stroke mm	130mm/130 mm
Front Brake	300mm twin discs, four-piston radial caliper, J.Juan
Rear Brake	240mm single disc, single-piston sliding caliper, J. Juan
ABS	standard
Traction Control	standard, two-level adjustable, switchable
<b>DIMENSIONS &amp; WEIGHT</b>	
LxWxH mm	2020x728x1105
Steering Angle	36°
Rake °	23.7°
Trail mm	93.2 mm
Wheelbase mm	1400 mm
Seat Height mm	810mm (830mm/795 with accessory seats)
Ground Clearance mm	140 mm
Fuel Tank Capacity L	15 L
Net Weight	175 kg
<b>ELECTRONICS</b>	
Dash	5-inch curved TFT display, CFMOTO Ride App connectivity
Battery	12V
Day-Running-Light	LED
Key	Mechanical Key
Quickshifter	Upshifting
Tire pressure monitor	accessory
Headlight	LED animated
Taillight	LED
Signal Light	LED
USB Charge Portal	USB Type-A & Type-C
Action camera control	standard
Steering stabilizer	accessory
Heated grips	accessory
OTA upgrade	standard
APP connectivity	standard
T-BOX	Optional
<b>Color</b>	
	n.a.