HARLEY-DAVIDSON

MODEL YEAR 2027 | H-D SPRINT™ 440

Dimensions	SP440 Harley-Davidson™ Sprint 440	
Length (*Cert)	2,145 mm (84.4 in.)	
Overall Width (*Cert)	815 mm (32.1 in.)	
Overall Height (*Cert)	1,108 mm (43.6 in.)	
Seat Height, Laden	N/A	2
Seat Height, Laden (Low seat position)		
Seat Height, Laden (High seat position)		
Seat Height, Laden (Low seat position with optional ARH suspension)		
Seat Height, Laden (High seat position with optional ARH suspension)		
Seat Height, Unladen (*Cert)	683 mm (26.9 in.)	
Seat Height, Unladen (Low seat position)		
Seat Height, Unladen (High seat position)		
Seat Height, Unladen (Low seat position with optional ARH suspension)		
Seat Height, Unladen (High seat position with optional ARH suspension)		
Static Ground Clearance (*Cert)	147 mm (5.7 in.)	
Static Ground Clearance without ARH (*Cert)		
Static Ground Clearance with ARH (*Cert)		
Dynamic Ground Clearance (with optional suspension)		
Rake (steering head) (deg)	27.6	
Fork Angle (deg)	30	
Trail	108.3 mm (4.26 in.)	
Wheelbase (*Cert)	1,450 mm (57.1 in.)	
Tires, Type	MRF	
Tires, Front Model	Zapper-FH	
Tires, Front Specification	100/90-19	
Tires, Rear Model	Steel Brace SC-01	
Tires, Rear Specification	150/60ZR17	

Fuel Capacity	9 l (2.4 gal.)	
Reserve Fuel Capacity, Fuel Injection (warning light)	3.78 l (1 gal.)	
Oil Capacity (w/filter)	2.25 l (2.38 qt.)	
Transmission Capacity	N/A	
Primary Chain Case Capacity	N/A	
Coolant Capacity	N/A	
Weight, As Shipped (*Cert)	181 kg (400 lb.)	
Weight, In Running Order (*Cert)	187 kg (412 lb.)	
Gross Vehicle Weight Rating (*Cert)	361 kg (795 lb.)	
Gross Axle Weight Rating, Front (*Cert)	124 kg (273 lb.)	
Gross Axle Weight Rating, Rear (*Cert)	237 kg (522 lb.)	
Luggage Capacity -Volume	N/A	

Engine	**SP440 Harley-Davidson™ Sprint 440**	
Engine	440 Single	
Valves	4 cycle, oil cooler, chain, Gear driven counter balancer	
Bore (*Cert)	79.6 mm (3.13 in.)	
Stroke (*Cert)	88.4 mm (3.48 in.)	
Displacement (*Cert)	440 cc (26.9 cu in)	
Compression Ratio (*Cert)	9.65:1	
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)	3
Air Cleaner	wet paper pleated type	
Exhaust	1-into-1; catalyst in header	
Lubrication System	Pressurized, dry-sump	

Drivetrain	**SP440 Harley-Davidson™ Sprint 440**	
Primary Drive (*Cert)	2.308	
Final Drive (*Cert)	2.6	
Clutch	Constant mech, foot shift	
Transmission	6-Speed Cruise Drive®	
Gear Ratios (overall) 1st (*Cert)	2.833	

Gear Ratios (overall) 2nd (*Cert)	1.875	
Gear Ratios (overall) 3rd (*Cert)	1.4	
Gear Ratios (overall) 4th (*Cert)	1.136	
Gear Ratios (overall) 5th (*Cert)	0.958	
Gear Ratios (overall) 6th (*Cert)	0.818	

Chassis	**SP440 Harley-Davidson™ Sprint 440**	
Frame	Steel tube trellis	
Swingarm	Mild steel, rectangular tube section, stamped x-member	
Front Fork	43mm Inverted Cartridge Forks	
Front Fork, Optional		
Rear Shocks	Monotube Piggy-Back Coil over Shocks with 7-step preload adjustment	
Rear Shocks, Optional		
Wheels, Optional Style Type	N/A	4
Wheels, Front Type	Black, 10-Spoke Cast Aluminum	4
Wheels, Front Diameter	19 in. (483 mm)	
Wheels, Front Width	2.5 in. (64 mm)	
Wheels, Rear Type	Black, 10-Spoke Cast Aluminum	4
Wheels, Rear Diameter	17 in. (432 mm)	
Wheels, Rear Width	4 in. (101.6 mm)	
Brakes, Caliper Type	Front: 2-piston; Rear: Single piston	
Brakes, Rotor Type	Front: single rotor fixed, hub mounted; Rear: Fixed hub mount	
Brakes, Front Diameter	320 mm (12.6 in.)	
Brakes, Front Thickness	5 mm (0.197 in.)	
Brakes, Front is dual	No	
Brakes, Rear Diameter	240 mm (9.45 in.)	
Brakes, Rear Thickness	4.5 mm (0.177 in.)	
Brakes, Anti-Lock Braking System (ABS)	Standard	
Suspension Travel, Front	130 mm (5.1 in.)	
Suspension Travel, Rear	76 mm (3 in.)	

Performance	SP440 Harley-Davidson™ Sprint 440	
Engine Torque Testing Method (*Cert)	J1349	
Engine Torque (*Cert)	38 Nm (28 ft-lb)	5
Engine Torque (rpm) (*Cert)	4000	
Power (Hp/kW) (*Cert)	27 Hp/ 20 kW	
Lean Angle Testing Method	SAE J1168	
Lean Angle, Right (deg.)	31	
Lean Angle, Left (deg.)	31	

Electric	SP440 Harley-Davidson™ Sprint 440	
Battery	12 V, 8 aH 110 CCA	
Charging	27 amp (325 W)	
Starting	Ignition Timing – Not Adjustable	
Lights (as per country regulation), Headlamp	All LED headlamp, low & high beam with signature position lighting	
Lights (as per country regulation), Tail/Stop	All LED rear lighting	
Lights (as per country regulation), Front Signal Lights	LED bullet turn signals	
Lights, Rear Turn Signals	LED bullet turn signals	
Gauges	3.5-inch (89 mm) viewable area TFT display with speedometer, gear, odometer, fuel level, clock, trip, side stand down alert, TIP over alert, range and tachometer indication.	
Auxiliary Lamps	N/A	
Electric Power Outlet	USB Port – 5 V, 2 A maximum Output	
GPS System	N/A	
Reverse	N/A	

Fuel Economy	SP440 Harley-Davidson™ Sprint 440	
Fuel Economy Testing Method	Estimated City/Hwy	
Fuel Economy	3.1 l/100 km (75.8 mpg)	
CO_2 Emissions Testing Method	WMTC	
CO_2 Emissions	73 g/km CO_2	

Infotainment	SP440 Harley-Davidson™ Sprint 440	
Infotainment system	N/A	
Screen Size	N/A	
Type	N/A	
Watts Per Channel	N/A	
Watts per Channel	N/A	
Speakers	N/A	
Speaker Size	N/A	
Headset Specifications (if equipped)	N/A	
AM	N/A	
FM	N/A	
MW	N/A	
LW	N/A	
Weather Band (WB)	N/A	
SD Card, Flash Drive and MP3 - via USB Connection	N/A	
Hands-free Mobile Phone - via Bluetooth	N/A	
Rider/Passenger Intercom	N/A	
Vehicle Information Screen (Air temperature, oil pressure and EITMS)	N/A	
Text-to-Speech (TTS) Languages	N/A	
USB	USB-C	
Phone Connectivity	N/A	
Bluetooth	N/A	
Navigation - via Bluetooth	N/A	

Rider Safety Enhancements	SP440 Harley-Davidson™ Sprint 440	
Anti-lock Brake System (ABS)	Included	
Electronic Linked Braking (ELB)	N/A	
Traction Control System (TCS)	N/A	
Drag-torque Slip Control System (DSCS)	N/A	
Vehicle Hold Control (VHC)	N/A	
Tire Pressure Monitoring System (TPMS)	N/A	
Wheel Lift Mitigation	N/A	

Cornering Rider Safety Enhancements	SP440 Harley-Davidson™ Sprint 440	
Cornering Enhanced Anti-lock Brake System (C-ABS)	N/A	
Cornering Enhanced Electronic Linked Braking (C-ELB)	N/A	
Cornering Enhanced Traction Control System (C-TCS)	N/A	
Cornering Drag-Torque Slip Control System (C-DSCS)	N/A	
Enhanced Lift Mitigation	N/A	

Warranty And Service	SP440 Harley-Davidson™ Sprint 440	
Warranty	24 months (unlimited mileage)	6
Service Interval	First 500 miles (750 km), every 5,000 miles (8,000 km) thereafter	7

Footnotes	SP440 Harley-Davidson™ Sprint 440	
1	Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.	

2	Measurement reflects 180 lb. (81.7 kg) operator weight.	
3	Recommended 91 octane or higher fuel (R+M)/2.	
4	Standard and optional wheels may vary by country and region.	
5	Values shown are nominal. Performance may vary by country and region.	
6	See motorcycle owner’s manual for complete details.	
7	Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner’s Manual for full details.	

©2026 H-D or its affiliates. HARLEY-DAVIDSON, HARLEY, H-D, and the Bar and Shield Logo are among the trademarks of H-D U.S.A., LLC. Third-party trademarks are the property of their respective owners.