

TECHNICAL DATA
RR 50 MOTARD TRACK

CHASSIS

Frame	steel double cradle frame
Wheel base	1390 mm
Max length	2000 mm
Max width	805 mm
Max height	1155 mm
Seat height	900 mm
Ground clearance	315 mm
Footrest height	365 mm
Dry weight	85 kg
Fuel tank capacity	6,5 l.
Reserve	1 l.
Cooling system capacity	620 cc
Front suspension	Hydraulic fork with ø41 mm USD
Rear suspension	Monoshock
Shock absorber stroke	62,5 mm
Front wheel travel	190 mm
Rear wheel travel	240 mm
Front brake	disc ø260 mm
Rear brake	disc ø220 mm
Front rim	2,50 x 17
Rear rim	3,50 x 17
Front tyre	100/80 - 17
Rear tyre	130/70 - 17

ENGINE

Type	Single-cylinder, 2-stroke, liquid cooled, lamellar induction in the crankcase
Bore	40,3 mm
Stroke	39 mm
Displacement	49,7cc
Compression ratio	12:1
Ignition	Electronic Moric 12v - 100W
Spark plug	NGK BR9 ES
Lubrication	Mixing with mechanical pump, fuel 1,5% (with synthetic oil)
Feeding	with carburettor
Carburettor	Dell'Orto PHBN 16 HS
Clutch	wet multi-disc clutch
Primary trasmission	Z. 20/71
Transmission	6 speed
Secondary Trasmission	Z. 11/50
Engine oil	SAE 20W/30 (820c)