

CHIEF BOBBER DARK HORSE SPECIFICATIONS

ENGINE: THUNDERSTROKE 116

Air-Cooled 49° V-twin

103.2mm x 113mm Wet, multi-plate

116 cu in / 1890 cc

Belt drive, 146 tooth

Closed loop / 54 mm bore

Telescopic fork with covers, 46 mm diameter,

Shrouded dual gas-charged monotube shocks

with adjustable preload, 75 mm travel

304 kg / 315 kg (As Shipped/Running Order)

Gear drive wet clutch

156 Nm at 3,300 rpm

132 mm travel

1626 mm

28.5°

662 mm

125 mm

526 kg

2286 mm

29° / 132 mm

Dual exhaust

Semi-dry sump

15.1 litres

5.68 litres

11.0 : 1

6-speed, constant mesh / foot shift

12 volts / 18 amp/hour, 310 CCA with quick connect charge port

Engine Type Transmission Battery Bore x Stroke Clutch Compression Ratio Displacement Exhaust Final Drive Lubrication System Fuel Capacity Fuel System Oil Capacity Primary Drive Peak Torque

SUSPENSION

Front Suspension

Rear Suspension

CHASSIS

Wheelbase Rake/Trail Lean Angle (Soft) Seat Height Weight Ground Clearance GVWR Length

BRAKES

Brake System Type Front Braking System Rear Braking System WHEELS & TIRES

Individual front and rear control with standard ABS Single 4 piston caliper / 300 mm semi-floating rotor Single 2 piston caliper / 300 mm floating rotor Front TireMetzeler® Cruisetec® 130/90 B16 73HFront WheelBlack Wire 16" x 3"Rear TireMetzeler® Cruisetec® 180/65 B16 81HRear WheelBlack Wire 16" x 5"

STANDARD FEATURES

Lighting	LED Headlight, LED Tail/Brake/Turn Signals
Gauges	101 mm Display Powered by RIDE COMMAND
	with Navigation* and Bluetooth®
Controls	Cruise Control, 3 Selectable Ride Modes,
	Keyless Ignition, ABS Standard, USB Charge Port

COLORS

Black Smoke Storm Gray

For pricing and availability in your region, please contact your local Indian Motorcycle press contact. Images may show North American models and may have accessories fitted. International models may vary. *Navigation may not be available in all countries.

