Nama	700MT
Name	700MT
Regulation	EURO V+
Engine name	283MU
Engine name	
Engine type	Twin Cylinder,DOHC 693cc
Displacement Bore x Stroke	83×64.0mm
Max Power	
	50KW/9500rpm
Max Torque	60N.m/6000rpm 11.6:1
Compression Ratio	1.5.1
Clutch type	Wet Mult slip cluth
Throttle Type	Mechanical Throttle
Chassis	0. 17.1
Frame	Steel Tube
Handlebar	One-piece reducer
Rear fork	Dual swing arm(aluminium alloy)
Wheel	aluminium alloy
Front Wheel	MT2.50×19 110/80 R19 CST
Rear Wheel	MT4.25×17 150/70 R17 CST
Front Suspension	43mm inverted front fork YU'AN
Rear Suspension	adjustable damping YU'AN
Suspension Travel	150mm/148mm
Upper pump	HANGTE
Front brake	dual discs,Opposite piston calipers
Lower pump	HANGTE
Rear Brake	Single disc
ABS	Yes
Specification	
Overall mm	2244×932×1435
Steering angle°	35
Rake °	26
Caster mm	100mm
Wheelbase mm	1445
Seat height mm	800
Ground Clearance mm	190
Fuel Tank L	20
Net Weight kg	225
Others	
Speedmeter	5 "curved TFT, support WIFI MOTOPLAY OTA
Battery	12V/11.2Ah
	,

Front light	Automatic
Light	Full LED
Windshield	Standard manually adjustable
Handguard	Yes
Heated Grip	STANDARD
Heated Seat	STANDARD
Key	Mechanical key
Rear Rack	Steel Rack
Front bumper	STANDARD
Engine Guard	STANDARD
TPMS	Yes
USB	Yes
T-BOX	STANDARD