

SUPER CHIEF DARK HORSE SPECIFICATIONS

ENGINE: THUNDERSTROKE 116

Engine Type Transmission Battery Bore x Stroke Clutch Compression Pa

Compression Ratio Displacement Exhaust Final Drive Lubrication System Fuel Capacity Fuel System Oil Capacity Primary Drive Peak Torque

Air-Cooled 49° V-twin 6-speed, constant mesh / foot shift 12 volts / 18 amp/hour, 310 CCA with quick connect charge port 103.2mm x 113mm Wet, multi-plate 11.0 : 1 116 cu in / 1890 cc Dual exhaust Belt drive, 146 tooth Semi-dry sump 15.1 litres Closed loop / 54 mm bore 5.68 litres Gear drive wet clutch 156 Nm at 3,300 rpm

132 mm travel

1626 mm 29° / 132 mm

28.5°

665 mm

125 mm

526 kg 2286 mm

36.6 litres

SUSPENSION

Front Suspension

Rear Suspension

CHASSIS

Wheelbase Rake/Trail Lean Angle (Soft) Seat Height Weight Ground Clearance GVWR Length Storage Capacity

BRAKES

Brake System Type Front Braking System Rear Braking System WHEELS & TIRES

Individual front and rear control with ABS Single 4 piston caliper / 300 mm semi-floating rotor Single 2 piston caliper / 300 mm floating rotor

Telescopic fork with covers, 46 mm diameter,

Dual gas-charged monotube shocks with adjustable preload, 75 mm travel

324 kg / 335 kg (As Shipped/Running Order)

Front Tire	Metzeler [®] Cruisetec [®] 130/90 B16 73H
Front Wheel	Wire Wheel 16" x 3"
Rear Tire	Metzeler [®] Cruisetec [®] 180/65 B16 81H
Rear Wheel	Wire Wheel 16" x 5"

STANDARD FEATURES

LED Headlight, LED Tail/Brake/Turn Signals
101 mm Display Powered by RIDE COMMAND
with Navigation* and Bluetooth®
Cruise Control, 3 Selectable Ride Modes,
Keyless Ignition, ABS, USB Charge Port

COLORS

Black Metallic Moss Green

For pricing and availability in your region, please contact your local Indian Motorcycle press contact. Images may show North American models and may have accessories fitted. International models may vary. *Navigation may not be available in all countries.

