

S1 125

BEYOND NORMAL, MEANING NO MORE TO ADD
S1 HAS ALL YOU NEED



S1

- BLACK / MUD BLACK
- SHASTA WHITE
- LIGHT RED



Tough All-round Player
Sturdy front look featured with shield-shaped headlight



Handy Instrument Panel
Simple arrangement for all information at once



Convenience
Nicely-located prominent fuel cap for easy refueling



Spacious Storage Space
Enough space for a half face helmet and belongings



Comfort Backrest
Secure riding position for passenger



2015 KOREA SCOOTER RACE CHAMPIONSHIP



LAP

TIME



STEEZER S

STEEZER

S3 Advance(250cc)

S3(125cc)

AROMA 125

S1 125

CA 110

Engine	SOHC, water cooled 4 stroke	SOHC, water cooled 4 stroke	DOHC, water cooled 4 stroke	DOHC, water cooled 4 stroke	SOHC, air cooled 4 stroke	SOHC, oil/air cooled 4 stroke	SOHC, air cooled 4 stroke
Displacement	124.9cc	124.9cc	247.0cc	124.1cc	124.6cc	124.9cc	108.9cc
Max Power	9.2kW@8,000rpm	9.2kW@8,000rpm	18.4kW@8,700rpm	10.3kW@9,250rpm	6.1kW@7,600rpm	8.5kW@8,700rpm	5.4kW@7,500rpm
Max Torque	11.8Nm@6,500rpm	11.8Nm@6,500rpm	21.3Nm@6,800rpm	10.9Nm@7,250rpm	8.9Nm@6,000rpm	10.5Nm@7,200rpm	9.1Nm@4,750rpm
Ignition System	Fuel Injection	Fuel Injection	Fuel Injection	Fuel Injection	Carburetor	Fuel Injection	Carburetor
Length x Width x Height(mm)	2,078 x 755 x 1,304	2,078 x 755 x 1,304	2,140 x 750 x 1,330	2,110 x 750 X 1,200	1,850 x 674 x 1,120	1,965 x 740 x 1,120	1,930 x 660 x 1,080
Wheel Base (mm)	1,382	1,382	1,500	1,500	1,280	1,350	1,220
Seat Height (mm)	790	740	745	745	740	770	765
Dry Weight (kg)	152	147	167	159	110	127	96
Fuel Capacity (L)	9.6	9.6	12.7	12.7	5.9	9.5	4
Transmission Type	V-matic	V-matic	V-matic	V-matic	V-matic	V-matic	4 Step Rotary
Suspension	Telescopic / Swing arm	Telescopic / Swing arm	Telescopic / Swing arm	Telescopic / Swing arm	Telescopic / Swing arm	Telescopic / Swing arm	Telescopic / Swing arm
Tires (F/R)	120/70-14, 140/60-14	120/70-14, 140/60-14	120/70-14 61S, 140/60-13 63S	120/70-14 61L, 140/60-13 63S	110/70-12, 3.50-10	120/70-13 53L, 130/60-13 60L	2.75-16-4, 3.00-16-6
Brakes (F/R)	Disc / Disc	Disc / Disc	Disc / Disc	Disc / Disc	Disc / Drum	Disc / Disc	Disc / Drum

DART 125

WITTY 50

BEAGLE 50

DAYSTAR 250

DAYSTAR 125

ROADWIN 250R

ROADWIN 125R

Engine	SOHC, air cooled 4 stroke	SOHC, air cooled 4 stroke	SOHC, air cooled 4 stroke	DOHC water-cooled 4 stroke	SOHC, oil/air cooled 4 stroke	DOHC, water cooled 4 stroke	DOHC, water cooled 4 stroke
Displacement	124.6cc	49.6cc	49.6cc	247.0cc	124.9cc	247.0cc	124.1cc
Max Power	6.1kW@7,600rpm	2.9kW@7,250rpm	2.9kW@7,250rpm	17.0kW@8,500rpm	9.4kW@9,700rpm	17.3kW@9,000rpm	10.9kW@10,500rpm
Max Torque	8.5Nm@6,000rpm	3.8Nm@6,500rpm	3.8Nm@6,500rpm	20.6Nm@6,700rpm	10.5Nm@8,000rpm	18.9Nm@7,000rpm	11.8Nm@8,500rpm
Ignition System	Carburetor	Carburetor	Carburetor	Fuel Injection	Fuel Injection	Fuel Injection	Fuel Injection
Length x Width x Height(mm)	1,870 x 670 x 1,075	1,800 x 710 x 1,185	1,800 x 710 x 1,185	2,200 x 845 x 1,130	2,040 x 860 x 1,155	2,025 x 778 x 1,180	2,025 x 778 x 1,180
Wheel Base (mm)	1,250	1,255	1,255	1,500	1,505	1,390	1,390
Seat Height (mm)	735	735	735	720	720	780	780
Dry Weight (kg)	110	95	95	165	154	158	145
Fuel Capacity (L)	5.9	5	5	17.0	16.8	15.0	15.0
Transmission Type	V-matic	V-matic	V-matic	5 step Return	5 step Return	5 step Return	5 step Return
Suspension	Telescopic / Swing arm	Telescopic / Swing arm	Telescopic / Swing arm	Telescopic / Swing arm	Telescopic / Swing arm	Telescopic / Swing arm	Telescopic / Swing arm
Tires (F/R)	110/70-12, 3.50-10	110/70-12, 120/70-12	110/70-12, 120/70-12	90/90-18, 130/90-15	90/90-18 15P, 130/90-15 66P	110/70-17 54S, 140/60-17 69S	110/70-17 54S, 140/60-17 69S
Brakes (F/R)	Disc / Disc	Disc / Drum	Disc / Drum	Double Disc / Disc	Disc / Disc	Double Disc / Disc	Disc / Disc