HARLEY-DAVIDSON

# MODEL YEAR 2027 | SUPER GLIDE®

| Dimensions | FXD Super Glide® | |
|---|---|---|
| Length (*Cert) | 91.3 in. (2,320 mm) | |
| Overall Width (*Cert) | 36.4 in. (925 mm) | |
| Overall Height (*Cert) | 45.7 in. (1,160 mm) | |
| Seat Height, Laden | 25.2 in. (640 mm) | 2 |
| Seat Height, Laden (Low seat position) | | |
| Seat Height, Laden (High seat position) | | |
| Seat Height, Laden (Low seat position with optional ARH suspension) | | |
| Seat Height, Laden (High seat position with optional ARH suspension) | | |
| Seat Height, Unladen (*Cert) | 26.6 in. (675 mm) | |
| Seat Height, Unladen (Low seat position) | | |
| Seat Height, Unladen (High seat position) | | |
| Seat Height, Unladen (Low seat position with optional ARH suspension) | | |
| Seat Height, Unladen (High seat position with optional ARH suspension) | | |
| Static Ground Clearance (*Cert) | 4.7 in. (120 mm) | |
| Static Ground Clearance without ARH (*Cert) | | |
| Static Ground Clearance with ARH (*Cert) | | |
| Dynamic Ground Clearance (with optional suspension) | | |
| Rake (steering head) (deg) | 30 | |
| Fork Angle (deg) | 30 | |
| Trail | 6.2 in. (157 mm) | |
| Wheelbase (*Cert) | 64.2 in. (1,630 mm) | |
| Tires, Type | Dunlop® Harley-Davidson Series, bias blackwall front and rear | |
| Tires, Front Model | D401F | |
| Tires, Front Specification | 100/90B19,57H,BW | |
| Tires, Rear Model | D401T | |

| | | |
|---|---|---|
| Tires, Rear Specification | 150/80B16,77H,BW | |
| Fuel Capacity | 5 gal. (18.9 l) | |
| Reserve Fuel Capacity, Fuel Injection (warning light) | 1 gal. (3.8 l) | |
| Oil Capacity (w/filter) | 5 qt. (4.7 l) | |
| Transmission Capacity | 1 qt. (0.95 l ) | |
| Primary Chain Case Capacity | 1.25 qt. (1.18 l ) | |
| Coolant Capacity | N/A | |
| Weight, As Shipped (*Cert) | 626 lb. (284 kg) | |
| Weight, In Running Order (*Cert) | 655 lb. (297 kg) | |
| Gross Vehicle Weight Rating (*Cert) | 1,160 lb. (526 kg) | |
| Gross Axle Weight Rating, Front (*Cert) | 450 lb. (204 kg) | |
| Gross Axle Weight Rating, Rear (*Cert) | 730 lb. (331 kg) | |
| Luggage Capacity -Volume | N/A | |

| **Engine** | **FXD Super Glide®** | |
|---|---|---|
| Engine | Milwaukee-Eight® 117 Classic | |
| Valves | Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; four valves per cylinder | |
| Bore (*Cert) | 4.075 in. (103.5 mm) | |
| Stroke (*Cert) | 4.5 in. (114.3 mm) | |
| Displacement (*Cert) | 117 cu in (1,923 cc) | |
| Compression Ratio (*Cert) | 10.3:1 | |
| Fuel System | Electronic Sequential Port Fuel Injection (ESPFI) | 3 |
| Air Cleaner | 9 in. (229 mm) round, center bolt cover with washable fiberglass filter media | |
| Exhaust | 2-into-1; catalyst in header | |
| Lubrication System | Pressurized, dry-sump with oil cooler | |

| **Drivetrain** | **FXD Super Glide®** | |
|---|---|---|
| Primary Drive (*Cert) | Chain, 34/46 ratio | |
| Final Drive (*Cert) | Belt, 32/66 ratio | |
| Clutch | Mechanical, 10 plate wet, assist & conventional | |
| Transmission | 6-Speed Cruise Drive® | |

| | | |
|---|---|---|
| Gear Ratios (overall) 1st (*Cert) | 9.311 | |
| Gear Ratios (overall) 2nd (*Cert) | 6.454 | |
| Gear Ratios (overall) 3rd (*Cert) | 4.793 | |
| Gear Ratios (overall) 4th (*Cert) | 3.882 | |
| Gear Ratios (overall) 5th (*Cert) | 3.307 | |
| Gear Ratios (overall) 6th (*Cert) | 2.79 | |

| **Chassis** | **FXD Super Glide®** | |
|---|---|---|
| Frame | Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; MIG welded; aluminum forged fender supports | |
| Swingarm | Mild steel, tubular sections, stamped x-member, forged axle junctions; MIG welded; removable belt spacer | |
| Front Fork | Dual-bending valve 49 mm telescopic with aluminum fork triple clamps; dual rate spring | |
| Front Fork, Optional | | |
| Rear Shocks | Hidden, free piston, coil-over monoshock; 43mm stroke; hydraulic preload adjustment | |
| Rear Shocks, Optional | | |
| Wheels, Optional Style Type | N/A | 4 |
| Wheels, Front Type | Chrome aluminum tubeless laced wheel | 4 |
| Wheels, Front Diameter | 19 in. (483 mm) | |
| Wheels, Front Width | 2.5 in. (64 mm) | |
| Wheels, Rear Type | Chrome aluminum tubeless laced wheel | 4 |
| Wheels, Rear Diameter | 16 in. (406 mm) | |
| Wheels, Rear Width | 3 in. (76 mm) | |
| Brakes, Caliper Type | 4-piston fixed front and 2-piston floating rear | |
| Brakes, Rotor Type | Solid, uniform expansion rotors | |
| Brakes, Front Diameter | 11.8 in. (300 mm) | |
| Brakes, Front Thickness | 0.2 in. (5 mm) | |
| Brakes, Front is dual | No | |
| Brakes, Rear Diameter | 11.5 in. (292 mm) | |
| Brakes, Rear Thickness | 0.23 in. (5.8 mm) | |
| Brakes, Anti-Lock Braking System (ABS) | Standard | |
| Suspension Travel, Front | 5 in. (130 mm) | |
| Suspension Travel, Rear | 3.4 in. (86 mm) | |

| Performance | FXD Super Glide® | |
|---|---|---|
| Engine Torque Testing Method (*Cert) | J1349 | |
| Engine Torque (*Cert) | 120 ft-lb (163 Nm) | 5 |
| Engine Torque (rpm) (*Cert) | 2500 | |
| Power (Hp/kW) (*Cert) | 98 HP / 73 kW @ 4600 rpm | |
| Lean Angle Testing Method | J1168 | |
| Lean Angle, Right (deg.) | 28.5 | |
| Lean Angle, Left (deg.) | 28.5 | |

| Electric | FXD Super Glide® | |
|---|---|---|
| Battery | Sealed, maintenance-free, absorbed glass mat (AGM) battery, 12V, 17.5Ah, 310 CCA at 0°F | |
| Charging | Three-phase, 48 Amp system (364 Watts @13 Volts, 900 rpm, 624 Watts max power @ 13 Volts, 2000 rpm) | |
| Starting | 1.6 kW electric with solenoid shift starter motor engagement | |
| Lights (as per country regulation), Headlamp | All LED, low beam, high beam and signature position lamp | |
| Lights (as per country regulation), Tail/Stop | Bullet-style, LED stop/tail/turn signals | |
| Lights (as per country regulation), Front Signal Lights | LED Bullet Turn Signals | |
| Lights, Rear Turn Signals | LED Bullet Turn Signals | |
| Gauges | 5-inch (127 mm) analog speedometer with digital gear, odometer, fuel level, ride modes, heated gear, traction control, ABS, TPMS, cruise control, clock, trip, range and tachometer indication | |
| Auxiliary Lamps | N/A | |
| Electric Power Outlet | USB C-Type , Output 5V at 2.4 Amp | |
| GPS System | N/A | |
| Reverse | N/A | |

| Fuel Economy | FXD Super Glide® | |
|---|---|---|
| Fuel Economy Testing Method | Estimated City/Hwy | |
| Fuel Economy | 47 mpg (5 l/100 km) | |

| Infotainment | FXD Super Glide® | |
|---|---|---|
| Infotainment system | N/A | |
| Screen Size | N/A | |
| Type | N/A | |
| Watts Per Channel | N/A | |
| Speakers | N/A | |
| Speaker Size | N/A | |
| Headset Specifications (if equipped) | N/A | |
| AM | N/A | |
| FM | N/A | |
| MW | N/A | |
| LW | N/A | |
| Weather Band (WB) | N/A | |
| SD Card, Flash Drive and MP3 - via USB Connection | N/A | |
| Hands-free Mobile Phone - via Bluetooth | N/A | |
| Languages | N/A | |
| Rider/Passenger Intercom | N/A | |
| Voice Recognition Languages: Phone functions only | N/A | |
| Voice Recognition Languages: Tuner/Media/Navigation | N/A | |
| Vehicle Information Screen (Air temperature, oil pressure and EITMS) | N/A | |
| Text-to-Speech (TTS) Languages | N/A | |
| USB | N/A | |
| Phone Connectivity | N/A | |
| Bluetooth | N/A | |
| Navigation | N/A | |

| Rider Safety Enhancements | FXD Super Glide® | |
|---|---|---|
| Anti-lock Brake System (ABS) | Included | |
| Electronic Linked Braking (ELB) | N/A | |
| Traction Control System (TCS) | Included | |
| Drag-torque Slip Control System (DSCS) | Included | |

| | | |
|---|---|---|
| Vehicle Hold Control (VHC) | N/A | |
| Tire Pressure Monitoring System (TPMS) | Included | |
| Wheel Lift Mitigation | N/A | |

| **Cornering  Rider Safety Enhancements** | **FXD Super Glide®** | |
|---|---|---|
| Cornering Enhanced Anti-lock Brake System (C-ABS) | Included | |
| Cornering Enhanced Electronic Linked Braking (C-ELB) | N/A | |
| Cornering Enhanced Traction Control System (C-TCS) | Included | |
| Cornering Drag-Torque Slip Control System (C-DSCS) | Included | |
| Enhanced Lift Mitigation | N/A | |

| **Warranty And Service** | **FXD Super Glide®** | |
|---|---|---|
| Warranty | 24 months (unlimited mileage) | 6 |
| Service Interval | First 1,000 miles (1,600 km), every 5,000 miles (8,000 km) thereafter | 7 |

| **Footnotes** | **FXD Super Glide®** | |
|---|---|---|
| 1 | Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please | |

| | | |
|---|---|---|
| | check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty. | |
| 2 | Measurement reflects 180 lb. (81.7 kg) operator weight. | |
| 3 | Recommended 91 octane or higher fuel (R+M)/2. | |
| 4 | Standard and optional wheels may vary by country and region. | |
| 5 | Values shown are nominal. Performance may vary by country and region. | |
| 6 | See motorcycle owner’s manual for complete details. | |
| 7 | Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner’s Manual for full details. | |

©2026 H-D or its affiliates. HARLEY-DAVIDSON, HARLEY, H-D, and the Bar and Shield Logo are among the trademarks of H-D U.S.A., LLC. Third-party trademarks are the property of their respective owners.